

PassleaderVCE

PassLeaderVCE

HOME

ALL VENDORS

★ GUARANTEE

? FAQ

TESTIMONIALS

CART (0)

Pass Your Next Certification Exam Fast!

Wonderful Certification Exam Guide and Exam Dumps - PassLeaderVCE

365 days free updates. First attempt guaranteed success.

Select a vendor...

Select an test...

Your email adress

Free Download Demo

We're not the only ones **happy** about PassLeaderVCE Practice Material ...

49316+ customers in 100+ countries use PassLeaderVCE Test Engine. Meet our customers.

VOREED

GetCustom

JET ORANGE

iCompany

Paradoxx

iMessenger



<http://www.passleadervce.com/>

Wonderful Certification Exam Guide and Exam Dumps- PassLeaderVCE

Exam : 650-472

Title : Introduction to 802.1X Operations
for Cisco Security Professionals
Exam (S802DT1X)

Vendors : Cisco

Version : DEMO

NO.1 Which two statements represent good use cases for Wake on LAN? (Choose two.)

- A. WoL can be used to power-up hosts for on-demand PXE booting.
- B. WoL can be used to power-up hosts for after-hours operating system updates and application patching.
- C. WoL can be used to power-up hosts to access the IPMI.
- D. WoL can be used to save electricity by powering down underused servers and desktops.

Answer: A,B

NO.2 Consider the example of an end user plugging an unmanaged third-party switch into a port in a conference room. If the wiring closet switch port requires 802.1X authentication (and the authentication host mode is set to the default), what would be the result of multiple 802.1X clients attempting to access the network from the unmanaged switch?

- A. After the first supplicant authenticates, other hosts connected to the unmanaged switch will be blocked from the network.
- B. After 802.1X times out three times, all hosts on the unmanaged switch will have access to the network.
- C. Up to eight hosts and one IP phone can be authenticated.
- D. After the first supplicant authenticates, all other hosts connected to the unmanaged switch have access to the network.

Answer: A

NO.3 Which two EAP methods are examples of challenge-response methods? (Choose two.)

- A. EAP-TLS
- B. PEAP
- C. EAP-FAST
- D. LEAP
- E. EAP-MD5

Answer: D,E

NO.4 Which option is a good example of a non-supplicant host?

- A. Laptop running Microsoft Windows 7
- B. IPprinter
- C. desktop PC running Ubuntu Linux

- D. IP camera
- E. Apple Macintosh running Mac OS X

Answer: B,D

NO.5 Which three RADIUS attributes are required to dynamically assign a VLAN? (Choose three)

- A. Attribute 65 (Tunnel-Medium-Type)
- B. Attribute 26 (Vendor-Specific)
- C. Attribute 64 (Tunnel-Type)
- D. Attribute 8 (Framed-IP-Address)
- E. Attribute 5 (NASPort)
- F. Attribute 81 (Tunnel-Private-Group-ID)

Answer: A,C,F

NO.6 Which statement correctly defines a persona?

- A. A Cisco ISE node can be configured as a primary or backup persona.
- B. Persona refers to collections of services running on a Cisco ISE node.
- C. A Cisco ISE node can be configured as a wired or wireless persona.
- D. Persona relates to the collection of 802.1X services configured on a Cisco Catalyst switch.
- E. Persona refers to the collection of EAP methods available to a supplicant.
- F. A Cisco ISE node can be configured as a standalone or distributed persona.

Answer: B

NO.7 Which two choices are valid methods of authorizing a wired supplicant? (Choose two.)

- A. EAP-FAST
- B. VLAN assignment
- C. dACL
- D. EAPOL
- E. RADIUS

Answer: B,C

NO.8 Which three modules are valid components of Cisco AnyConnect Secure Mobility Client for Windows?

(Choose three)

- A. Network Access Manager
- B. VPN Module
- C. Network Authentication Manager
- D. Telemetry and Profiling Module

- E. Profiling Module
- F. Posture Module
- G. Profiling Module

Answer: A,E,F

NO.9 Which two statements about MACsec security are true? (Choose two.)

- A. MACsec is an IEEE standard that is defined by 802.3AE.
- B. MACsec leverages an 802.1X EAP framework to negotiate the MACsec Key Agreement.
- C. MACsec is an IETF standard that is defined by RFC 4501.
- D. MACsec can negotiate a MACsec Key Agreement without 802.1X.
- E. MACsec is an IETF standard that is defined by RFC 4505.
- F. MACsec is an IEEE standard that is defined by 802.1AE.

Answer: B,F

NO.10 On a Cisco Catalyst switch, which default ports will the radius-server host command use for RADIUS

authentication and accounting messages?

- A. TCP - Authentication 1645/Accounting 1646
- B. TCP - Authentication 1535/Accounting 1536
- C. TCP - Authentication 1812/Accounting 1813
- D. UDP - Authentication 1535/Accounting 1536
- E. UDP - Authentication 1812/Accounting 1813
- F. UDP - Authentication 1645/Accounting 1646

Answer: E